# W-1

| Depth (feet) | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|
| | CONCRETE. | | |
| | SILTY GRAVELS, black (2.5Y 2.5/I), decomposed elastic rock fragments. | W-1-1.5' | |
| | CLAY (CL), dark grayish brown (2.5Y 3/2), moderate plasticity, slightly damp to damp, firm to stiff. | | 0-4 (0) |
| | - Color change to dark olive-brown (3/3). | W-1-3' | |
| 5 | | | 4-7 (0) |
| | | W-1-5' | |
| | - Grades to silty clay. | | |
| | | W-1-8' | 7-11 (0) |
| 10 | | | |
| | CLAYEY TO SILTY SAND (SC-SM), olive-brown (2.5Y 4/4), fine-grained, low plasticity, slightly damp to damp, medium dense to dense. | | 11-15 (0) |
| 15 | | | |
| | | | 15-19 (0) |
| | SAND (SP), olive-brown (2.5Y 4/4), fine-grained, damp to moist, medium dense to dense, gravel lens at 18.5. | | |
| | SILTY SAND, olive-brown (2.5Y 4/4), very fine-grained, low plasticity, damp to moist, medium dense to dense. | | |
| ▽ 20 | SAND (SW), olive-brown (2.5Y 4/3), fine to coarse-grained, wet, medium dense to dense. | | 9-23 |
| | SILTY SAND (SM), olive-brown (2.5Y 4/3), fine-grained, low plasticity, wet, medium dense to dense. | | |
| | CLAYEY SAND (SC), olive-brown (2.5Y 4/3), fine-grained, moderate plasticity, wet, dense. | | |
| | BOTTOM OF BORING AT 23 FEET. | | |
| 25 | | | |

SAND SILT CLAY GRAVEL

Drilling method: GeoProbe
Sampling method: Macro Core
Drilling date: 3/3/2005
Geologist: RM

Groundwater level ▽ At time of drilling

Soil Sample Collected — Soil Sample Recovery Interval

WEST Environmental Services & Technology

March 2005

DeSilva.Hayward

**Soil Boring Lithology for Boring No. W-1**

LITHOLOGY | SAMPLE DATA

| Depth (feet) | Graphic Log | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|---|
| **W-2** | | | | |
| | | CONCRETE, 6" | | |
| | | CLAYEY GRAVEL, dark grayish brown (2.5Y 4/2), low plasticity, very moist, loose to medium dense. | W-2-1' | 0-4 (0) |
| | | CLAYEY SAND (SC), dark bluish gray (5B 4/1), fine to coarse, low plasticity, damp to moist, medium dense to dense. | | |
| | | CLAY (CL-CH), black (2.5/I), moderate plasticity, damp to moist, firm to stiff. | W-2-3' | |
| 5 | | CLAYEY GRAVEL (GC), dark greenish gray (10Y 4/1), coarse-grained, low plasticity, damp to moist, loose to medium dense. | W-2-5' | 4-8 (0) |
| | | CLAY (CL), greenish black (10Y 2.5/I), moderate plasticity, damp to moist, firm to stiff. | | |
| | | BOTTOM OF BORING AT 8 FEET. | W-2-8' | |
| 10 | | | | |
| **W-3** | | | | |
| | | CONCRETE. | | |
| | | GRAVEL (GW), very dark greenish gray (10Y 3/1), coarse to fine-grained, slightly damp to damp, loose to medium dense. | W-3-1' | 0-4 (0) |
| | | CLAY (CL), black, low to moderate plasticity, damp to moist, firm to stiff. | | |
| | | - Gravel with tar like matrix. | W-3-3' | |
| 5 | | - Color change to very dark gray (2.5Y 3/1). | W-3-5' | 4-8 (0) |
| | | BOTTOM OF BORING AT 8 FEET. | W-3-8' | |
| 10 | | | | |

SAND | SILT | CLAY | GRAVEL

Drilling method: GeoProbe
Sampling method: Macro Core
Drilling date: 3/4/2005
Geologist: RM

Soil Sample Collected — Soil Sample Recovery Interval

WEST Environmental Services & Technology

March 2005

DeSilva.Hayward

# Soil Boring Lithology for Boring Nos. W-2 and W-3

LITHOLOGY | SAMPLE DATA

| Depth (feet) | Graphic Log | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|---|
| **W-4** | | | | |
| | | CONCRETE, 5". | | |
| | | BASEROCK. | | |
| | | GRAVELLY CLAY (CL-CH), black, moderate plasticity, slightly damp, very stiff, minor rock chips. | W-4-1' | |
| | | CLAY (CL-CH), black (2.5Y/I), moderate plasticity, damp to moist, firm to stiff. | | 0-4 (0) |
| | | | W-4-3' | |
| 5 | | | W-4-5' | |
| | | - Color change to very dark grayish brown (2.5Y 3/2), stiff to very stiff. | | 4-8 (0) |
| | | | W-4-8' | |
| | | BOTTOM OF BORING AT 8 FEET. | | |
| 10 | | | | |
| **W-5** | | | | |
| | | CONCRETE. | | |
| | | BASEROCK. | | |
| | | CLAY (CL-CH), black (7.5YR 2.5/I), moderate to high plasticity, slightly damp to damp, stiff to very stiff. | W-5-1' | |
| | | - Trace gravel and roots. | | 0-4 (0) |
| | | | W-5-3' | |
| 5 | | | W-5-5' | |
| | | - Color change to very dark grayish brown (2.5Y 3/2), stiff to very stiff. | | 4-8 (0) |
| | | | W-5-8' | |
| | | BOTTOM OF BORING AT 8 FEET. | | |
| 10 | | | | |

SAND | SILT | CLAY | GRAVEL

Drilling method: GeoProbe
Sampling method: Macro Core
Drilling date: 3/4/2005
Geologist: RM

Soil Sample Collected — Soil Sample Recovery Interval

WEST Environmental Services & Technology

March 2005

DeSilva.Hayward

# Soil Boring Lithology for Boring Nos. W-4 and W-5

LITHOLOGY | SAMPLE DATA

| Depth (feet) | Graphic Log | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|---|
| **W-6** | | | | |
| | | CONCRETE. | | |
| | | BASEROCK. | | |
| | | CLAY (CL), black (7.5YR 2.5/I), moderate plasticity, slightly damp to damp, firm to stiff. | W-6-1' | 0-4 (0) |
| | | - Gravel layer. | W-6-3' | |
| 5 | | | W-6-5' | 4-8 (0) |
| | | BOTTOM OF BORING AT 8 FEET. | W-6-8' | |
| 10 | | | | |
| **W-8** | | | | |
| | | CONCRETE. | | |
| | | BASEROCK. | | |
| | | - Decomposed gravel with tar like matrix at 1-2'. | W-8-1' | 0-4 (0) |
| | | CLAY (CL), black, moderate plasticity, slightly damp to damp, firm to stiff. | W-8-3' | |
| 5 | | | W-8-5' | 4-8 (0) |
| | | CLAYEY SILT (ML), dark yellowish brown (10YR 4/4), low plasticity, slightly damp to damp, stiff to very stiff. | W-8-8' | |
| | | BOTTOM OF BORING AT 8 FEET. | | |
| 10 | | | | |

SAND | SILT | CLAY | GRAVEL

Drilling method: GeoProbe
Sampling method: Macro Core
Drilling date: 3/4/2005
Geologist: RM

Soil Sample Collected — Soil Sample Recovery Interval

WEST Environmental Services & Technology

March 2005

DeSilva.Hayward

**Soil Boring Lithology for Boring Nos. W-6 and W-8**

# W-9

| Depth (feet) | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|
| | CONCRETE. | | |
| | CLAY (CL), black, moderate plasticity, slightly damp to damp, firm to stiff. | W-9-1.5' | 1.5-5 (0) |
| | | W-9-3' | |
| 5 | - Color change to very dark grayish brown (2.5Y 3/2), moderate to high plasticity. | | |
| | | W-9-5' | 5-8 (0) |
| | CLAYEY SILT (ML), olive-brown (2.5Y 4/3), low plasticity, slightly damp to damp, firm to stiff, minor fine-grained sand. | W-9-8' | |
| 10 | SILTY SAND (SM), olive-brown (2.5Y 4/3), fine-grained, low plasticity, slightly damp to damp, medium dense to dense. | | 8-12 (0) |
| 15 | | | 12-16 (0) |
| ▽ | GRAVELLY SAND (SW), dark yellowish brown (10YR 4/4), fine to coarse-grained, moist to very moist, medium dense to dense. | | 16-20 |
| | CLAYEY SAND (SC), dark yellowish brown (10YR 4/4), fine-grained, low plasticity, moist to very moist, medium dense to dense, minor gravel. | | |
| | SANDY CLAY (CL), dark yellowish brown (10YR 4/4), fine-grained, moderate plasticity, moist to very moist, firm to stiff. | | |
| 20 | SILTY SAND (SM), dark yellowish brown (10YR 4/4), fine-grained, low plasticity, very moist to wet, medium dense to dense. | | |
| | BOTTOM OF BORING AT 20 FEET. | | |
| 25 | | | |

SAND SILT CLAY GRAVEL

Drilling method: GeoProbe
Sampling method: Macro Core
Drilling date: 3/3/2005
Geologist: RM

Groundwater level ▽ At time of drilling

Soil Sample Collected — Soil Sample Recovery Interval

WEST Environmental Services & Technology

March 2005

DeSilva.Hayward

**Soil Boring Lithology for Boring No. W-9**

LITHOLOGY | SAMPLE DATA

| Depth (feet) | Graphic Log | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|---|
| **W-10** | | | | |
| | | CONCRETE. | | |
| | | BASEROCK. | | |
| | | CLAY (CH), black (2.5Y), moderate to high plasticity, slightly damp to damp, firm to stiff. | W-10-0.5' | 0-4 (0) |
| | | - Color change to very dark gray (2.5Y 3/1). | W-10-3' | |
| | | - Color change to dark olive-brown (3/3). | | |
| | | BOTTOM OF BORING AT 4 FEET. | | |
| 5 | | | | |
| 10 | | | | |
| **W-11** | | | | |
| | | ASPHALT. | | |
| | | CLAY (CH), black, moderate to high plasticity, slightly damp to damp, firm to stiff, oil coated soil. | W-11-0.5' | 0-4 (0) |
| | | - Color change to very dark brown (10YR 2/2). | W-11-3' | |
| | | - Color change to very dark grayish brown (2.5Y 3/2). | | |
| 5 | | | | |
| | | CLAYEY SILT (ML), dark yellowish brown (10YR 4/4), low to moderate plasticity, slightly damp to damp, firm to stiff. | W-11-5' | 4-8 (0) |
| | | SILTY SAND TO SANDY SILT (ML-SM), dark yellowish brown (10YR 4/4), low plasticity, fine-grained, damp to moist, firm to stiff. | W-11-8' | |
| | | BOTTOM OF BORING AT 8 FEET. | | |
| 10 | | | | |

SAND | SILT | CLAY | GRAVEL

Drilling method: GeoProbe
Sampling method: Macro Core
Drilling date: 3/3/2005
Geologist: RM

Soil Sample Collected — Soil Sample Recovery Interval

WEST Environmental Services & Technology

March 2005

DeSilva.Hayward

# Soil Boring Lithology for Boring Nos. W-10 and W-11

LITHOLOGY | SAMPLE DATA

| Depth (feet) | Graphic Log | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|---|
| **W-12** | | | | |
| | | ASPHALT. | | |
| | | CLAY (CH), black (2.5/I), moderate to high plasticity, slightly damp to damp, firm to stiff. | W-12-0.5' | 0-4 (0) |
| | | - Color change to very dark grayish brown (2.5Y 3/2). | W-12-3' | |
| 5 | | - Color change to olive-brown (4/3). | W-12-5' | |
| | | CLAYEY SAND (SC), dark olive-brown (3/3), fine-grained, low to moderate plasticity, slightly damp to damp,medium dense to dense. | | 4-8 (0) |
| | | SAND (SP), dark olive-brown (3/3), fine-grained, slightly damp to damp, medium dense to dense, trace gravel. | W-12-8' | |
| | | BOTTOM OF BORING AT 8 FEET. | | |
| 10 | | | | |
| **W-17** | | | | |
| | | CONCRETE. | | |
| | | BASEROCK. | W-17-1' | |
| | | CLAY (CH), black (2.5/I), moderate to high plasticity, slightly damp to damp, firm to stiff. | | 0-4 (0) |
| | | | W-17-3' | |
| 5 | | | W-17-5' | |
| | | - Color change to olive-brown (2.5Y 4/3). | | 4-8 (0) |
| | | BOTTOM OF BORING AT 8 FEET. | W-17-8' | |
| 10 | | | | |

SAND SILT CLAY GRAVEL

Drilling method: GeoProbe
Sampling method: Macro Core
Drilling date: 3/3/2005
Geologist: RM

Soil Sample Collected — Soil Sample Recovery Interval

WEST Environmental Services & Technology

March 2005

DeSilva.Hayward

# Soil Boring Lithology for Boring Nos. W-12 and W-17

LITHOLOGY | SAMPLE DATA

| Depth (feet) | Graphic Log | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|---|
| **W-26** | | | | |
| | | SANDY CLAY (CL), black (10YR 4/1), fine to medium-grained, medium dense, low to moderate plasticity, damp. | | |
| | | - Change color to very dark brown (10YR 2/2) at 1.5 feet. | | 0-4 (0.2) |
| 5 | | CLAY (CL), very dark gray (10YR 3/1), medium stiff to stiff, moderate to high plasticity, dry to damp at 5 feet. | | 4-8 (0) |
| | | BOTTOM OF BORING AT 8 FEET. | | |
| 10 | | | | |
| **W-27** | | | | |
| | | SANDY CLAY (CL), black (10YR 2/1), fine to medium-grained, medium dense, low to moderate plasticity, dry to damp. | | 0-4 (0.5) |
| 5 | | - Change color to very dark grayish brown (10YR 3/2), medium stiff to stiff, low to moderate plasticity, damp at 4 feet. | | |
| | | CLAY (CL), black (10YR 4/1), stiff to very stiff, moderate to high plasticity, damp. | | 4-8 (0) |
| | | SANDY CLAY (SC), very dark grayish brown (10YR 3/2), stiff to very stiff, moderate to high plasticity, damp. | | |
| | | - Change color to dark yellowish brown (10YR 3/4) at 7 feet. BOTTOM OF BORING AT 8 FEET. | | |
| 10 | | | | |

SAND | SILT | CLAY | GRAVEL

Drilling method: Direct Push
Sampling method: Macro Core
Drilling date: 3/2/2006
Geologist: SS

WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

# Soil Boring Lithology for Boring Nos. W-26 and W-27

# W-28

| Depth (feet) | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|
| | LITHOLOGY | | SAMPLE DATA |
| 0 | CLAY (CL), black (10YR 2/1), soft to medium stiff, high plasticity, dry to damp. | | 0-4 (0) |
| | - Increase percentage sand to clay to sandy clay, low to moderate plasticity, dark brown (10YR 3/3), dry to damp at 3 feet. | | |
| 5 | | | 4-8 (0) |
| | SANDY CLAY (SC), dark yellowish brown (10YR 3/4), medium dense, low to moderate plasticity, dry. | | |
| | - Change color to very dark brown (10YR 2/2), damp at 8 feet. | | |
| 10 | CLAYEY SAND (SC), dark yellowish brown (10YR 3/4), medium dense, fine to medium-grained, damp. | | 8-12 (0) |
| | SAND (SP), dark yellowish brown (10YR 3/4), fine to medium-grained, loose, damp. | | 12-16 (0) |
| 15 | | | |
| | CLAY (CL), dark yellowish brown (10YR 4/4), soft, moderate to high plasticity, moist. | | 16-20 (0) |
| | SAND (SP), dark yellowish brown (10YR 4/4), loose to medium dense, wet. | | |
| 20 | BOTTOM OF BORING AT 20 FEET. | | |
| 25 | | | |

SAND SILT CLAY GRAVEL

Drilling method: Direct Push
Sampling method: Macro Core
Drilling date: 3/2//2006
Geologist: SS

Groundwater level
Measured at time of drilling

WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

**Soil Boring Lithology for Boring No. W-28**

# W-29

| Depth (feet) | Graphic Log | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|---|
| | | LITHOLOGY | | SAMPLE DATA |
| | | CLAYEY SAND (SC), with rounded gravel to 1 cm, dark yellowish brown (10YR 3/4), loose to medium dense, fine to coarse-grained sand, moist. | | |
| | | SAND (SP), black (10YR 2/1), medium to coarse-grained, loose, wet. | | |
| | | CLAY (CL), very dark brown (10YR 2/2), medium stiff to stiff, moderate to high plasticity, dry to damp. | | 0-4 (0) |
| 5 | | | 5 | |
| | | | | 4-8 (0) |
| | | - Change to soft, 10-percent coarse sand, wet at 8 feet. | | |
| 10 | | | 10 | 8-12 (0) |
| | | CLAYEY SAND (SC), olive-gray (5Y 4/2), fine to medium-grained, loose to medium dense, moist. | | |
| | | - Increase grain size to coarse, wet, loose at 12.5 feet. | | |
| | | | | 12-16 (0) |
| ▽ 15 | | SANDY CLAY (CL), olive-gray (5Y 4/2), medium dense to dense, moist to wet. | 15 | |
| | | | | 16-20 (0) |
| 20 | | BOTTOM OF BORING AT 20 FEET. | 20 | |
| 25 | | | 25 | |

SAND SILT CLAY GRAVEL

Drilling method: Direct Pushy
Sampling method: Macro Core
Drilling date: 3/2/2006
Geologist: RM

Groundwater level
▽ Measured at time of drilling

WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

**Soil Boring Lithology for Boring No. W-29**

# W-30

| Depth (feet) | Description | Sample No. & Interval | (OVM) Core Interval, Ft. |
|---|---|---|---|
| | CLAY (CL), black (10YR 2/1), soft to medium stiff, high plasticity, dry to damp. | | 0-4 (0) |
| | - Increase percentage sand to clay to sandy clay, low to moderate plasticity, dark brown (10YR 3/3), dry to damp at 3 feet. | | |
| 5 | | 5 | |
| | CLAYEY SAND (SC), dark yellowish brown (10YR 4/4), medium dense, fine to medium-grained, damp. | | 4-8 (0) |
| | SAND (SP), dark yellowish brown (10YR 4/6), loose to medium dense, fine to medium-grained, dry to damp. | | |
| 10 | | 10 | 8-12 (0) |
| | | | 12-16 (0) |
| 15 | - 3" SANDY CLAY at 15 feet. | 15 | |
| | - 2" coarse sand, loose at 16 feet. CLAYEY SAND (SC), dark yellowish brown (10YR 4/6), moderately dense, fine to medium-grained, moist. | | 16-20 (0) |
| 20 | - 2" loose sand at 19.5 feet. | 20 | |
| | BOTTOM OF BORING AT 20 FEET. | | |
| 25 | | 25 | |

SAND SILT CLAY GRAVEL

Drilling method: Direct Push
Sampling method: Macro Core
Drilling date: 3/2/2006
Geologist: SS

Groundwater level
Measured at time of drilling

WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

**Soil Boring Lithology for Boring No. W-30**

| WELL CONSTRUCTION | LITHOLOGY | | SAMPLE DATA | |
|---|---|---|---|---|
| Depth (feet) | Graphic Log | Description | Sample Interval & Penetration Rate, Blows/ft. | (PID) & Core Interval, ft. |
| | | SANDY CLAY (SC) TO CLAYEY SAND (SC), black (5Y 2.5/2), soft, low to moderate plasticity, damp to moist. | | 0-5 (0) |
| 5 | | SANDY CLAY (SC), very dark grayish brown, fine to medium-grained, medium dense, low plasticity, dry to damp. | 5 | 5-8 (0) |
| | | SAND (SP), dark yellowish brown (10YR 3/6), loose, fine to medium-grained, dry to damp.<br>- Change to loose to medium dense at 7 feet.<br>- Loose, dry to damp. | | |
| 10 | | SAND (SW), fine to coarse-grained, with pale gray rounded gravel to 2 centimeters. | 10 | 8-12 (0) |
| | | SAND (SP), dark yellowish brown (10YR 3/6), loose, fine to medium-grained, dry to damp.<br>- Includes dark gray rounded gravel to 2 centimeters at 13 feet. | | 12-16 (0) |
| 15 | | SILTY SAND TO SAND, dark yellowish brown (10YR 3/6), loose to medium dense, moist.<br>- Change to fine to medium sand, dark yellowish brown (10YR 3/6), loose, moist at 15.5 feet. | 15 | |
| | | SAND (SW), fine to coarse-grained with black rounded gravel to 1 centimeter, moist.<br>- Change to fine to medium sand, dark yellowish brown (10YR 3/6), loose, moist at 16 feet. | | 16-20 (0) |
| 20 | | SANDY CLAY (CL), olive-brown (2.5Y 4/4), medium to high plasticity, soft, moist.<br>- Change to fine to medium sand, dark yellowish brown (10YR 3/6), loose, wet at 18.5 feet.<br>- Slight increase in grain size to medium-grained, gravel at 6" for 2", angular, loose, wet at 20 feet. | 20 | |
| | | SANDY CLAY (CL), olive-brown (2.5Y 4/3), loose to medium dense, soft, wet, medium to high plasticity. | | 20-24 (0) |
| 25 | | SAND (SP), olive-brown (2.5 4/4), fine to medium-grained, loose wet. | 25 | |
| | | SILTY CLAY (CL), olive-brown (2.5Y 4/4), medium dense to dense, damp to moist, black organics. | | 24-27 (0) |
| | | BOTTOM OF BORING AT 27 FEET. | | |




SAND SILT CLAY GRAVEL

Drilling method: HSA 8" Ø
Sampling method: Direct Push
Drilling date: 3/1/2006
Geologist: SS

Groundwater level
At time of drilling
Measured on 3/3/06

WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

**Well Construction & Soil Boring Lithology for Boring No. MW-1**

| WELL CONSTRUCTION | LITHOLOGY | | SAMPLE DATA | |
|---|---|---|---|---|
| Depth (feet) | Graphic Log | Description | Sample Interval & Penetration Rate, Blows/ft. | (PID) & Core Interval, ft. |
| Well box; 8-inch diameter borehole; Cement grout | | SILTY SAND (SM) TO CLAYEY SAND (SC), dark olive-brown (2.5Y 3/3), fine to medium grained, medium dense, dry to damp. | | 0-5 (0) |
| 3/4 inch diameter blank Schedule 40 PVC casing; 3.25-inch diameter borehole | | CLAYEY SAND (SC), dark yellowish brown (10YR 3/4), fine to medium-grained sand, medium dense to dense, low plasticity, black staining on outer layer of core, dry to damp. - Change color to yellowish brown (10YR 4/6) at 7 feet. | | 5-8 (0) |
| Bentonite seal | | SAND (SP), yellowish brown (10YR 4/6), loose, fine to medium-grained, dry to damp. | | 8-12 (0) |
| 3/4 inch diameter slotted Schedule 40 PVC casing | | SILTY SAND (SM) TO SAND (SP), yellowish brown (10YR 4/6), loose, dry to damp. | | 12-16 (0) |
| #2/12 Sand | | CLAY (CL), olive-brown (2.5Y 5/4), soft to medium soft, high plasticity, dry to damp. | | 16-20 (0) |
| | | SAND (SP), olive-brown (2.5Y 5/4), fine to medium-grained, loose to medium dense, wet. SANDY CLAY (CL), olive-brown (2.5Y 4/4), soft, high plasticity, moist. | | 20-24 (0) |
| | | CLAY (CL), very dark grayish brown (2.5Y 3/2), soft to medium dense, damp to moist, moderate to high plasticity. - Soft. | | 24-27 (0) |
| End cap | | - Change color to olive-brown (2.5Y 4/4), medium firm to firm, damp to moist, black organic fragments at 26 feet. BOTTOM OF BORING AT 27 FEET. | | |

SAND SILT CLAY GRAVEL

Drilling method: HSA 8" Ø
Sampling method: Direct Push
Drilling date: 3/1/2006
Geologist: SS

Groundwater level
At time of drilling
Measured on 3/3/06

WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

# Well Construction & Soil Boring Lithology for Boring No. MW-2




WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

**Well Construction & Soil Boring Lithology for Boring No. MW-3**




SAND SILT CLAY GRAVEL

Drilling method: HSA 8" Ø
Sampling method: Direct Push
Drilling date: 3/2/2006
Geologist: SS

Groundwater level
At time of drilling
Measured on 3/3/06

WEST Environmental Services & Technology

March 2006

DeSilva.Hayward

**Well Construction & Soil Boring Lithology for Boring No. MW-4**